



MODEL	COLOR	CCT / λ_d	VOLTAGE	LUMINOUS FLUX	No. LED	POWER
HB18LA-6W24	○ BIANCO FREDDO - COOL WHITE	6500/7000 K	24V DC	1280 Lm	6	15 W

CARATTERISTICHE DEL PRODOTTO

- Barra a LED adatta per cassonetti luminosi bifacciali
- La barra è dotata di connettori di qualità per il collegamento ad altre barre
- Lenti da 15°- 60° per una diffusione luminosa perfetta
- Driver a corrente costante a bordo scheda per la stabilità ed omogeneità del flusso luminoso
- Facilità di fissaggio, adesivo e fori per le viti.

PRODUCT FEATURES

- LED bar suited for double sided sign-boxes
- The bar is equipped with high quality connectors, it allow to connect the bars to each other.
- Lens 15°- 60° degrees for a perfect light diffusion
- The constant current driver on board for the stability and homogeneity luminous flux
- Easy fixing, by adhesive and holes for the screws.

TECHNICAL DATA

PCB	ALLUMINIO	No. barre per confezione - No. bars for packaging	1
Protezione - Protection	IP30	No. Barre collegabili in successione - No. Max. bars	8
Temperatura esercizio - Operating Temp. Range	-30 C° ~ +60 C°	CRI - Color Rendering Index	80
Temperatura stoccaggio - Storage Temp. Range	-30 C° ~ +70 C°	Angolo del flusso luminoso - Beam angle	15°- 60°

